



Automated Workstation Pre-NAT II

Fully automated system for nucleic acid extraction and PCR set-up



- Fully automated system for nucleic acid extraction for up to 96 primary samples and pipetting of up to 288 PCRs per run
- Established system for nucleic acid extraction based on magnetic particles
- Integrated cooling unit for PCR reagents and plates and for automated preparation of PCR master mixes
- Versatile further use of PCRs possible; optimised for EUROArray and EUROReal-Time workflows
- Precise pipetting with disposable filter tips and efficient and resource-friendly dispensing system for extraction reagents
- User-friendly instrument software with graphic visualisation of all processes
- Excellent service from EUROIMMUN – your contact for everything from test systems to instruments and software



The **Automated Workstation Pre-NAT II** is a system for fully automated nucleic acid extraction and subsequent pipetting of PCRs. The extraction of nucleic acids is carried out using magnetic particles. These are transferred successively into the automatically dispensed reagents by means of magnetisable metal rods. The liquid handling module then automatically pipettes the required PCRs from the isolated nucleic acids and the PCR reagents stored cooled in the instrument.



System

Sample capacity up to 96 samples
 Sample tubes..... outer diameter of 12–16mm, height up to 100mm
 Sample material e.g. blood, smears, urine, hair and skin samples
 Barcode identification automated for sample tubes with all commercial barcode types
 Automatic sterilisation..... UV light

Pipetting unit

Pipettors 4 pipettors for disposable pipette tips, with liquid level detection
 Pipetting volume 4–800 µl, in increments of 1 µl
 Accuracy..... measurement deviation ± 5% (≥ 4 µl–≤ 20 µl); ± 2% (> 20 µl–≤ 800 µl)
 Precision CV ≤ 5% (≥ 4 µl–≤ 20 µl); CV ≤ 2% (> 20 µl–≤ 800 µl)
 Reagent positions..... for up to 28 PCR reagents
 Cooling of reagents..... to 2–8 °C
 Test capacity up to 3x96 PCRs per run, up to 3 different pipetting schemes per run

Extraction unit

Extraction kit chemagic Total NA Extraction Kit H96 (ZM 9126-0960) for 960 reactions
 Method extraction using magnetic particles
 Separation magnetisable metal rods with disposable sleeves, rotation platform
 Dispensing module..... 200 µl–10 ml; measurement deviation of ≤ 12%
 Liquid level detection for reagents and liquid waste

Characteristics

Operating system Microsoft Windows 10 Pro (64 bits)
 Communication with EURORealTime Analysis software via XML
 Language..... English
 Dimensions/Weight 1510 mm × 845 mm × 1690 mm (W × D × H) / approx. 350 kg
 Power supply 220V, 50Hz, 3150VA incl. PC and cooling unit